

PRODUCT-DETAILS

3GJM183430-BEH

M3JM 180MLC 6



General Information

Product ID	3GJM183430-BEH
ABB Type Designation	M3JM 180MLC 6
Catalog Description	M3JM 180MLC 6

Additional Information

ABB Type Designation	M3JM 180MLC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	18.50 kW	975 r/min	33.00 A	0.740	90.10 %	181.10 N·m	7.50

Gross Weight	323 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 90.1 % Partial Load (75%) 90.1 %

	Partial Load (50%) 88.5 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 180MLC 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	313 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

