

PRODUCT-DETAILS

3GJM201410-BDL

M3JM 200MLA 2



General Information

Product ID	3GJM201410-BDL
ABB Type Designation	M3JM 200MLA 2
Catalog Description	M3JM 200MLA 2

Additional Information

ABB Type Designation	M3JM 200MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312M/C3
Bearing NDE	6310M/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	30.00 kW	2957 r/min	30.50 A	0.880	93.30 %	96.92 N-m	7.50
D	--	50 Hz	400 V	30.00 kW	2957 r/min	52.40 A	0.880	93.30 %	96.92 N-m	7.50
D	--	50 Hz	415 V	30.00 kW	2961 r/min	51.10 A	0.870	93.30 %	96.80 N-m	8.10

Gross Weight	353 kg
--------------	--------

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 93.3 % Partial Load (75%) 93.6 % Partial Load (50%) 93.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 92.4 % Partial Load (75%) 92.4 % Partial Load (50%) 91.2 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 200MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	343 kg
Product Type	5JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

