


PRODUCT-DETAILS

3GJM202410-ADL  
M3JM 200MLA 4



| General Information  |                |
|----------------------|----------------|
| Product ID           | 3GJM202410-ADL |
| ABB Type Designation | M3JM 200MLA 4  |
| Catalog Description  | M3JM 200MLA 4  |

| Additional Information |               |
|------------------------|---------------|
| ABB Type Designation   | M3JM 200MLA 4 |
| Altitude               | 1000 m        |
| Ambient Temperature    | 40 °C         |
| Bearing                | 6312/C3       |
| Bearing NDE            | 6310/C3       |
| Country of Origin      | Finland (FI)  |
| Customs Tariff Number  | 85015230      |
| EX-Protection          | Exdb          |
| Electrical Data        |               |

| Conn | Temp Class | Freq  | Voltage | Power    | Speed      | Current | Power Factor | Efficiency | Torque     | IS/IN |
|------|------------|-------|---------|----------|------------|---------|--------------|------------|------------|-------|
| Y    | --         | 50 Hz | 690 V   | 30.00 kW | 1483 r/min | 31.90 A | 0.840        | 93.60 %    | 193.20 N·m | 7.50  |
| D    | --         | 50 Hz | 400 V   | 30.00 kW | 1483 r/min | 54.80 A | 0.840        | 93.60 %    | 193.20 N·m | 7.50  |
| D    | --         | 50 Hz | 415 V   | 30.00 kW | 1485 r/min | 53.60 A | 0.830        | 93.60 %    | 193.00 N·m | 8.00  |
| D    | --         | 60 Hz | 440 V   | 30.00 kW | 1784 r/min | 49.50 A | 0.850        | 94.10 %    | 160.60 N·m | 7.50  |
| D    | --         | 60 Hz | 460 V   | 30.00 kW | 1785 r/min | 47.70 A | 0.840        | 94.10 %    | 160.50 N·m | 8.20  |

|                           |                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------|
| Gross Weight              | 381 kg                                                                                            |
| IC Class                  | IC411                                                                                             |
| IE Class Data (50 Hz)     | IE Class IE3<br>Full Load (100%) 93.6 %<br>Partial Load (75%) 93.8 %<br>Partial Load (50%) 93.1 % |
| IE Class Data (60 Hz)     | IE Class IE3<br>Full Load (100%) 94.1 %<br>Partial Load (75%) 94.1 %<br>Partial Load (50%) 93.1 % |
| IM Class                  | IMB3 IM1001                                                                                       |
| IP Class                  | IP66                                                                                              |
| Insulation Class          | ICLF                                                                                              |
| Invoice Description       | M3JM 200MLA 4                                                                                     |
| Made To Order             | No                                                                                                |
| Minimum Order Quantity    | 1 piece                                                                                           |
| Number of Poles (High)    | 4                                                                                                 |
| Order Multiple            | 1 piece                                                                                           |
| Package Level 1 Units     | 0 pallet (lift)                                                                                   |
| Product Name              | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight        | 371 kg                                                                                            |
| Product Type              | 5JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor                                                |
| Quote Only                | No                                                                                                |
| Selling Unit of Measure   | piece                                                                                             |
| Temperature Class Default | --                                                                                                |
| Terminator Box Location   | Top                                                                                               |
| Two Speed Motor           | No                                                                                                |
| Type of Duty              | S1                                                                                                |
| UNSPSC                    | 26101100                                                                                          |
| Voltage Code              | D                                                                                                 |
| WEEE Category             | 4. Large Equipment (Any External Dimension More Than 50 cm)                                       |

## Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

