

PRODUCT-DETAILS

3GJM202410-BEK

M3JM 200MLA 4



General Information

Product ID	3GJM202410-BEK
ABB Type Designation	M3JM 200MLA 4
Catalog Description	M3JM 200MLA 4

Additional Information

ABB Type Designation	M3JM 200MLA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	30.00 kW	1484 r/min	44.10 A	0.840	94.40 %	193.00 N·m	8.40
D	--	60 Hz	575 V	30.00 kW	1786 r/min	38.90 A	0.830	94.70 %	160.00 N·m	9.60

Gross Weight	388 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 94.4 % Partial Load (75%) 94.8 % Partial Load (50%) 94.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 94.7 % Partial Load (75%) 94.8 % Partial Load (50%) 94.0 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 200MLA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	378 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

