

PRODUCT-DETAILS

3GJM252210-BSK

M3JM 250SMA 4



General Information

Product ID	3GJM252210-BSK
ABB Type Designation	M3JM 250SMA 4
Catalog Description	M3JM 250SMA 4

Additional Information

ABB Type Designation	M3JM 250SMA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6315/C3
Bearing NDE	6313/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	55.00 kW	1485 r/min	97.80 A	0.850	95.40 %	353.00 N·m	7.90
D	--	50 Hz	230 V	55.00 kW	1485 r/min	170.00 A	0.850	95.40 %	353.00 N·m	7.90
Y	--	50 Hz	380 V	55.00 kW	1482 r/min	102.00 A	0.860	95.00 %	353.00 N·m	7.20
D	--	50 Hz	220 V	55.00 kW	1482 r/min	177.00 A	0.860	95.00 %	353.00 N·m	7.20
Y	--	50 Hz	415 V	55.00 kW	1486 r/min	95.20 A	0.840	95.60 %	353.00 N·m	8.50
Y	--	60 Hz	460 V	55.00 kW	1787 r/min	85.80 A	0.840	95.70 %	293.00 N·m	9.10

Gross Weight	518 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 95.0 % Partial Load (75%) 95.7 % Partial Load (50%) 95.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.7 % Partial Load (75%) 95.8 % Partial Load (50%) 95.2 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 250SMA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	508 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

