

PRODUCT-DETAILS

3GJM253210-BEK

M3JM 250SMA 6



General Information

Product ID	3GJM253210-BEK
ABB Type Designation	M3JM 250SMA 6
Catalog Description	M3JM 250SMA 6

Additional Information

ABB Type Designation	M3JM 250SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6315/C3
Bearing NDE	6313/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	37.00 kW	991 r/min	54.80 A	0.830	94.40 %	356.00 N·m	7.50
D	--	60 Hz	575 V	37.00 kW	1192 r/min	48.10 A	0.820	94.50 %	296.00 N·m	8.40

Gross Weight	553 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE3
	Full Load (100%) 94.4 %
	Partial Load (75%) 94.9 %
	Partial Load (50%) 94.7 %
IE Class Data (60 Hz)	IE Class IE3
	Full Load (100%) 94.5 %
	Partial Load (75%) 94.7 %
	Partial Load (50%) 94.1 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 250SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	543 kg
Product Type	3JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	Top
Two Speed Motor	No
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

