

PRODUCT-DETAILS

# 3GJM312230-BDL

## M3JM 315SMC 4



### General Information

|                      |                |
|----------------------|----------------|
| Product ID           | 3GJM312230-BDL |
| ABB Type Designation | M3JM 315SMC 4  |
| Catalog Description  | M3JM 315SMC 4  |

### Additional Information

|                       |               |
|-----------------------|---------------|
| ABB Type Designation  | M3JM 315SMC 4 |
| Altitude              | 1000 m        |
| Ambient Temperature   | 40 °C         |
| Bearing               | 6319/C3       |
| Bearing NDE           | 6316/C3       |
| Country of Origin     | Finland (FI)  |
| Customs Tariff Number | 85015381      |
| Direction of Rotation | Both sides    |
| EX-Protection         | Exdb          |

#### Electrical Data

| Conn | Temp Class | Freq  | Voltage | Power     | Speed      | Current  | Power Factor | Efficiency | Torque     | IS/IN |
|------|------------|-------|---------|-----------|------------|----------|--------------|------------|------------|-------|
| Y    | --         | 50 Hz | 690 V   | 132.00 kW | 1488 r/min | 134.00 A | 0.860        | 95.60 %    | 847.00 N·m | 6.70  |
| D    | --         | 50 Hz | 400 V   | 132.00 kW | 1488 r/min | 231.00 A | 0.860        | 95.60 %    | 847.00 N·m | 6.70  |
| D    | --         | 50 Hz | 415 V   | 132.00 kW | 1489 r/min | 225.00 A | 0.850        | 95.60 %    | 846.00 N·m | 7.20  |

|                           |                                                                                                   |
|---------------------------|---------------------------------------------------------------------------------------------------|
| Gross Weight              | 1145 kg                                                                                           |
| IC Class                  | IC411                                                                                             |
| IE Class Data (50 Hz)     | IE Class IE3<br>Full Load (100%) 95.6 %<br>Partial Load (75%) 95.7 %<br>Partial Load (50%) 95.2 % |
| IE Class Data (60 Hz)     | IE Class IE2<br>Full Load (100%) 95.0 %<br>Partial Load (75%) 94.9 %<br>Partial Load (50%) 94.1 % |
| IM Class                  | IMB5 IM3001                                                                                       |
| IP Class                  | IP66                                                                                              |
| Insulation Class          | ICLF                                                                                              |
| Invoice Description       | M3JM 315SMC 4                                                                                     |
| Made To Order             | No                                                                                                |
| Minimum Order Quantity    | 1 piece                                                                                           |
| Number of Poles (High)    | 4                                                                                                 |
| Order Multiple            | 1 piece                                                                                           |
| Package Level 1 Units     | 0 pallet (lift)                                                                                   |
| Product Name              | 3-Phase squirrel cage motor                                                                       |
| Product Net Weight        | 1125 kg                                                                                           |
| Product Type              | 5JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor                                                |
| Quote Only                | No                                                                                                |
| Selling Unit of Measure   | piece                                                                                             |
| Temperature Class Default | --                                                                                                |
| Terminator Box Location   | D-End top                                                                                         |
| Two Speed Motor           | No                                                                                                |
| Type of Duty              | S1                                                                                                |
| UNSPSC                    | 26101100                                                                                          |
| Voltage Code              | D                                                                                                 |
| WEEE Category             | 4. Large Equipment (Any External Dimension More Than 50 cm)                                       |

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors



