

PRODUCT-DETAILS

3GJM312230-BSG

M3JM 315SMC 4



General Information

Product ID	3GJM312230-BSG
ABB Type Designation	M3JM 315SMC 4
Catalog Description	M3JM 315SMC 4

Additional Information

ABB Type Designation	M3JM 315SMC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	160.00 kW	1487 r/min	284.00 A	0.850	95.30 %	1027.00 N·m	7.20
D	--	50 Hz	230 V	160.00 kW	1487 r/min	494.00 A	0.850	95.30 %	1027.00 N·m	7.20
Y	--	50 Hz	415 V	160.00 kW	1488 r/min	277.00 A	0.840	95.40 %	1027.00 N·m	8.60
Y	--	60 Hz	460 V	160.00 kW	1788 r/min	249.00 A	0.850	95.20 %	854.00 N·m	8.20

Gross Weight	1043 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.3 % Partial Load (75%) 95.3 % Partial Load (50%) 94.8 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 95.2 % Partial Load (75%) 95.0 % Partial Load (50%) 94.0 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 315SMC 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1023 kg
Product Type	3JM2__M3JM_IE2_Group_I Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

