

PRODUCT-DETAILS

3GJM313230-BEL

M3JM 315SMC 6



General Information

Product ID	3GJM313230-BEL
ABB Type Designation	M3JM 315SMC 6
Catalog Description	M3JM 315SMC 6

Additional Information

ABB Type Designation	M3JM 315SMC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	500 V	90.00 kW	994 r/min	130.00 A	0.840	94.90 %	864.00 N·m	7.20

Gross Weight	1116 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3

	Full Load (100%) 94.9 % Partial Load (75%) 95.1 % Partial Load (50%) 94.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.0 % Partial Load (75%) 94.9 % Partial Load (50%) 93.8 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 315SMC 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1096 kg
Product Type	5JM3__M3JM_IE3_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE3 Premium Efficiency Mining Motors

