


PRODUCT-DETAILS

3GJM314220-BDG

M3JM 315SMB 8



General Information

Product ID	3GJM314220-BDG
ABB Type Designation	M3JM 315SMB 8
Catalog Description	M3JM 315SMB 8

Additional Information

ABB Type Designation	M3JM 315SMB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	75.00 kW	741 r/min	84.80 A	0.820	93.00 %	966.00 N·m	7.10
D	--	50 Hz	400 V	75.00 kW	741 r/min	146.00 A	0.820	93.00 %	966.00 N·m	7.10
D	--	50 Hz	415 V	75.00 kW	742 r/min	142.00 A	0.810	93.00 %	966.00 N·m	7.60

Gross Weight	977 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.0 % Partial Load (75%) 93.2 % Partial Load (50%) 93.0 %
IM Class	IMB5 IM3001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 315SMB 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	957 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

