

PRODUCT-DETAILS

3GJM351230-ASG

M3JM 355SMC 2



General Information

Product ID	3GJM351230-ASG
ABB Type Designation	M3JM 355SMC 2
Catalog Description	M3JM 355SMC 2

Additional Information

ABB Type Designation	M3JM 355SMC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316M/C3
Bearing NDE	6316M/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	355.00 kW	2982 r/min	603.00 A	0.880	95.70 %	1136.00 N·m	7.20
D	--	50 Hz	230 V	355.00 kW	2982 r/min	1049.00 A	0.880	95.70 %	1136.00 N·m	7.20
Y	--	50 Hz	415 V	355.00 kW	2985 r/min	588.00 A	0.870	95.70 %	1135.00 N·m	7.90

Gross Weight	2004 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.7 % Partial Load (75%) 95.5 % Partial Load (50%) 94.7 %
IM Class	IMB3 IM1001
IP Class	IP66
Insulation Class	ICLF
Invoice Description	M3JM 355SMC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1974 kg
Product Type	3JM2__M3JM_IE2_Group_I_Flameproof_Exd_mining_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Mining Motors → Flameproof IE2 High Efficiency Mining Motors

