


PRODUCT-DETAILS

3GJP091030-CDH

M3JP 90SLC 2

For sale but "Obsolete", replaced by



General Information

Product ID	3GJP091030-CDH
ABB Type Designation	M3JP 90SLC 2
Catalog Description	M3JP 90SLC 2

Additional Information

ABB Type Designation	M3JP 90SLC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	2.20 kW	2876 r/min	2.47 A	0.890	83.70 %	7.30 N·m	7.80
D	T4	50 Hz	400 V	2.20 kW	2877 r/min	4.27 A	0.890	83.70 %	7.30 N·m	7.80
D	T4	50 Hz	415 V	2.20 kW	2886 r/min	4.15 A	0.890	83.70 %	7.28 N·m	8.40

Gross Weight	56 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 83.7 % Partial Load (75%) 84.1 % Partial Load (50%) 82.6 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 90SLC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GJP091030-BDH
Product Name	3-Phase squirrel cage motor
Product Net Weight	53 kg
Product Type	3JP2__M3JP_IE2_Flameproof_Exd_motor
Quote Only	No
Replaced Product ID (OLD)	3GJP091030-CDG
Replacement Product ID (NEW)	3GJP091030-CDJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



