


PRODUCT-DETAILS

3GJP092010-ASH

M3JP 90SLA 4

For sale but "Obsolete", replaced by



General Information

Product ID	3GJP092010-ASH
ABB Type Designation	M3JP 90SLA 4
Catalog Description	M3JP 90SLA 4

Additional Information

ABB Type Designation	M3JP 90SLA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015220
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	1.10 kW	1432 r/min	2.52 A	0.770	82.20 %	7.30 N·m	5.90
D	T4	50 Hz	230 V	1.10 kW	1430 r/min	4.40 A	0.770	82.20 %	7.30 N·m	5.90
Y	T4	50 Hz	415 V	1.10 kW	1438 r/min	2.41 A	0.740	82.20 %	7.20 N·m	6.10

Gas Group	IIB
Gross Weight	54 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 82.2 % Partial Load (75%) 81.7 % Partial Load (50%) 78.4 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 90SLA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	51 kg
Product Type	3JP2__M3JP_IE2_Flameproof_Exd_motor
Quote Only	No
Replaced Product ID (OLD)	3GJP092010-ASG
Replacement Product ID (NEW)	3GJP092020-ASJ
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



