

PRODUCT-DETAILS

3GJP131270-CFK

M3JP 132SMG 2



General Information

Product ID	3GJP131270-CFK
ABB Type Designation	M3JP 132SMG 2
Catalog Description	M3JP 132SMG 2

Additional Information

ABB Type Designation	M3JP 132SMG 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	500 V	7.50 kW	2907 r/min	10.50 A	0.900	91.30 %	24.70 N-m	8.10
Y	T4	60 Hz	575 V	7.50 kW	3518 r/min	9.10 A	0.900	91.60 %	20.40 N-m	9.30

Gross Weight	129 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 91.3 % Partial Load (75%) 92.1 % Partial Load (50%) 92.1 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.6 % Partial Load (75%) 91.6 % Partial Load (50%) 90.6 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 132SMG 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GJP131270-BFK
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	124 kg
Product Type	3JP3__M3JP_IE3_Flameproof_Exd_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	F
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors



