

PRODUCT-DETAILS

3GJP182430-ADH

HIGH OUTPUT



General Information

Product ID	3GJP182430-ADH
ABB Type Designation	M3JP 180MLC 4
Catalog Description	HIGH OUTPUT

Additional Information

ABB Type Designation	M3JP 180MLC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6310/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	30.00 kW	1466 r/min	34.40 A	0.810	92.10 %	194.50 N·m	7.60
D	T4	50 Hz	400 V	30.00 kW	1466 r/min	59.50 A	0.810	92.10 %	194.50 N·m	7.60
D	T4	50 Hz	415 V	30.00 kW	1468 r/min	59.40 A	0.780	91.40 %	194.00 N·m	8.00

Gross Weight	314 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 91.4 % Partial Load (75%) 91.5 % Partial Load (50%) 90.6 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	HIGH OUTPUT
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	304 kg
Product Type	3JP2__M3JP_IE2_Flamproof_Exd_motor
Quote Only	No
Replaced Product ID (OLD)	3GJP182430-ADG
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



