

PRODUCT-DETAILS

3GJP201410-BDG

M3JP 200MLA 2



General Information

Product ID	3GJP201410-BDG
ABB Type Designation	M3JP 200MLA 2
Catalog Description	M3JP 200MLA 2

Additional Information

ABB Type Designation	M3JP 200MLA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6312/C3
Bearing NDE	6310/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	30.00 kW	2956 r/min	31.00 A	0.880	92.80 %	96.90 N-m	7.10
D	T4	50 Hz	400 V	30.00 kW	2956 r/min	52.70 A	0.880	92.80 %	96.90 N-m	7.00
D	T4	50 Hz	415 V	30.00 kW	2958 r/min	52.30 A	0.870	92.80 %	97.10 N-m	7.50

Gas Group	IIB
Gross Weight	320 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 92.8 % Partial Load (75%) 93.3 % Partial Load (50%) 92.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 200MLA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	310 kg
Product Type	3JP2__M3JP_IE2_Flameproof_Exd_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class	T4
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

