

PRODUCT-DETAILS

3GJP282220-AEK

M3JP 280SMB 4



General Information

Product ID	3GJP282220-AEK
ABB Type Designation	M3JP 280SMB 4
Catalog Description	M3JP 280SMB 4

Additional Information

ABB Type Designation	M3JP 280SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
EX-Protection	Exd

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T4	50 Hz	500 V	75.00 kW	1486 r/min	108.00 A	0.850	95.90 %	482.00 N·m	7.40
D	T4	60 Hz	575 V	75.00 kW	1788 r/min	93.50 A	0.840	95.90 %	401.00 N·m	8.40

Gross Weight	786 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 95.9 % Partial Load (75%) 96.2 % Partial Load (50%) 96.1 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.9 % Partial Load (75%) 95.7 % Partial Load (50%) 94.7 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 280SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	766 kg
Product Type	3JP3__M3JP_IE3_Flameproof_Exd_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors



