


PRODUCT-DETAILS

3GJP352220-AEK

M3JP 355SMB 4



General Information

Product ID	3GJP352220-AEK
ABB Type Designation	M3JP 355SMB 4
Catalog Description	M3JP 355SMB 4

Additional Information

ABB Type Designation	M3JP 355SMB 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T4	50 Hz	500 V	250.00 kW	1491 r/min	346.00 A	0.870	96.60 %	1601.00 N·m	7.80
D	T4	60 Hz	575 V	250.00 kW	1792 r/min	304.00 A	0.860	96.70 %	1332.00 N·m	8.80

Gross Weight	1980 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 96.6 % Partial Load (75%) 96.8 % Partial Load (50%) 96.5 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 96.7 % Partial Load (75%) 96.6 % Partial Load (50%) 96.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 355SMB 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1950 kg
Product Type	3JP3__M3JP_IE3_Flameproof_Exd_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

