


PRODUCT-DETAILS

3GJP353210-AEG

M3JP 355SMA 6



General Information

Product ID	3GJP353210-AEG
ABB Type Designation	M3JP 355SMA 6
Catalog Description	M3JP 355SMA 6

Additional Information

ABB Type Designation	M3JP 355SMA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T4	50 Hz	500 V	160.00 kW	993 r/min	233.00 A	0.830	95.40 %	1538.00 N·m	7.00

Gas Group	IIB
Gross Weight	1660 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.4 % Partial Load (75%) 95.6 % Partial Load (50%) 95.2 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 355SMA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1520 kg
Product Type	3JP2__M3JP_IE2_Flameproof_Exd_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

