

PRODUCT-DETAILS

3GJP353220-BDL

M3JP 355SMB 6



General Information

Product ID	3GJP353220-BDL
ABB Type Designation	M3JP 355SMB 6
Catalog Description	M3JP 355SMB 6

Additional Information

ABB Type Designation	M3JP 355SMB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exdb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	200.00 kW	993 r/min	213.00 A	0.820	95.80 %	1923.00 N·m	6.70
D	T4	50 Hz	400 V	200.00 kW	993 r/min	365.00 A	0.820	95.80 %	1923.00 N·m	6.70
D	T4	50 Hz	415 V	200.00 kW	993 r/min	358.00 A	0.810	95.80 %	1923.00 N·m	7.20

Gas Group	IIB
Gross Weight	1822 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 95.8 % Partial Load (75%) 96.0 % Partial Load (50%) 95.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 95.8 % Partial Load (75%) 95.8 % Partial Load (50%) 95.2 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 355SMB 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1792 kg
Product Type	5JP3__M3JP_IE3_Flameproof_Ext_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors



