


PRODUCT-DETAILS

3GJP454540-AEG

M3JP 450LD 8



General Information

Product ID	3GJP454540-AEG
ABB Type Designation	M3JP 450LD 8
Catalog Description	M3JP 450LD 8

Additional Information

ABB Type Designation	M3JP 450LD 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6326/C3
Bearing NDE	6322/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394
EX-Protection	Exdb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T4	50 Hz	500 V	630.00 kW	745 r/min	925.00 A	0.820	96.50 %	8075.00 N·m	7.60

Gas Group	IIB
Gross Weight	5000 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE4

	Full Load (100%) 96.5 %
	Partial Load (75%) 96.6 %
	Partial Load (50%) 96.1 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3JP 450LD 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	4960 kg
Product Type	3JP2__M3JP_IE2_Flameproof_Ext_motor
Quote Only	No
SCIP	297e96db-dbee-43c1-ad2d-ddd583080bb8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Terminator Box Location	Top
Two Speed Motor	No
Voltage Code	E
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

