

PRODUCT-DETAILS

3GKP081310-BEH

M3KP 80MA 2

For sale but "Obsolete", replaced by



General Information

Product ID	3GKP081310-BEH
ABB Type Designation	M3KP 80MA 2
Catalog Description	M3KP 80MA 2

Additional Information

ABB Type Designation	M3KP 80MA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
EX-Protection	Exde

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T4	50 Hz	500 V	0.75 kW	2877 r/min	1.27 A	0.850	80.10 %	2.40 N·m	7.10

Gas Group	IIB
Gross Weight	31 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2

	Full Load (100%) 80.0 %
	Partial Load (75%) 75.0 %
	Partial Load (50%) 79.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 80MA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	28 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP081310-BEG
Replacement Product ID (NEW)	3GKP081320-BEJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

