

PRODUCT-DETAILS

3GKP084320-CSH

No Description Available

For sale but "Obsolete", replaced by



General Information

Product ID	3GKP084320-CSH
ABB Type Designation	M3KP 80MB 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 80MB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
EX-Protection	Exde

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	0.25 kW	705 r/min	1.21 A	0.510	61.40 %	3.40 N·m	3.20
D	T4	50 Hz	230 V	0.25 kW	705 r/min	2.10 A	0.510	61.40 %	3.40 N·m	3.20
Y	T4	50 Hz	415 V	0.25 kW	708 r/min	1.23 A	0.490	60.60 %	3.38 N·m	3.30

Gas Group	IIB
Gross Weight	32 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2
	Full Load (100%) 60.6 %
	Partial Load (75%) 56.6 %
	Partial Load (50%) 48.7 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GKP084320-BSH
Product Name	3-Phase squirrel cage motor
Product Net Weight	29 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP084320-CSG
Replacement Product ID (NEW)	3GKP084320-CSJ
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



