

PRODUCT-DETAILS

3GKP091020-CEK

No Description Available



General Information

Product ID	3GKP091020-CEK
ABB Type Designation	M3KP 90SLB 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 90SLB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T4	50 Hz	500 V	1.50 kW	2892 r/min	2.20 A	0.890	86.40 %	4.80 N·m	7.30
D	T4	60 Hz	575 V	1.50 kW	3506 r/min	1.90 A	0.890	86.40 %	4.00 N·m	8.50

Gross Weight	53 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.4 % Partial Load (75%) 87.4 % Partial Load (50%) 86.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 86.4 % Partial Load (75%) 86.1 % Partial Load (50%) 83.7 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GKP091020-BEK
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	50 kg
Product Type	3KP3__M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors



