

PRODUCT-DETAILS

3GKP093030-ASJ

No Description Available



General Information

Product ID	3GKP093030-ASJ
ABB Type Designation	M3KP 90SLC 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 90SLC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	0.75 kW	960 r/min	2.30 A	0.580	76.30 %	7.40 N·m	4.50
D	T4	50 Hz	230 V	0.75 kW	960 r/min	4.10 A	0.580	76.30 %	7.40 N·m	4.50
Y	T4	60 Hz	460 V	0.75 kW	1160 r/min	2.10 A	0.540	78.20 %	6.10 N·m	5.10

Gross Weight	50 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 76.3 % Partial Load (75%) 74.7 % Partial Load (50%) 69.5 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 78.2 % Partial Load (75%) 75.7 % Partial Load (50%) 70.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	47 kg
Product Type	3KPO__M3JP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP093010-ASH
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



