

PRODUCT-DETAILS

3GKP093050-CDJ

No Description Available



General Information

Product ID	3GKP093050-CDJ
ABB Type Designation	M3KP 90SLE 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 90SLE 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	1.10 kW	930 r/min	1.63 A	0.720	78.10 %	11.20 N·m	4.00
D	T4	50 Hz	400 V	1.10 kW	930 r/min	2.82 A	0.720	78.10 %	11.20 N·m	4.00
D	T4	60 Hz	460 V	1.10 kW	1140 r/min	2.60 A	0.650	75.00 %	9.20 N·m	4.60

Gross Weight	52 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 78.1 % Partial Load (75%) 78.6 % Partial Load (50%) 76.5 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 75.0 % Partial Load (75%) 74.8 % Partial Load (50%) 72.0 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GKP093050-BDJ
Product Name	3-Phase squirrel cage motor
Product Net Weight	49 kg
Product Type	3KP0__M3JP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP093030-CDH
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



