

PRODUCT-DETAILS

3GKP093560-CSK

No Description Available



General Information

Product ID	3GKP093560-CSK
ABB Type Designation	M3KP 90LF 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 90LF 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6205-2Z/C3
Bearing NDE	6204-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	1.10 kW	944 r/min	2.62 A	0.750	81.00 %	11.10 N·m	4.70
D	T4	50 Hz	230 V	1.10 kW	944 r/min	4.50 A	0.750	81.00 %	11.10 N·m	4.70
Y	T4	50 Hz	380 V	1.10 kW	936 r/min	2.70 A	0.770	81.00 %	11.20 N·m	4.30
D	T4	50 Hz	220 V	1.10 kW	936 r/min	4.66 A	0.770	81.00 %	11.20 N·m	4.30
Y	T4	50 Hz	415 V	1.10 kW	949 r/min	2.50 A	0.730	81.00 %	11.10 N·m	5.00

Gas Group	IIB
Gross Weight	55 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 81.0 % Partial Load (75%) 81.7 % Partial Load (50%) 80.1 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 75.0 % Partial Load (75%) 76.2 % Partial Load (50%) 74.4 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GKP093560-BSK
Product Name	3-Phase squirrel cage motor
Product Net Weight	52 kg
Product Type	3KP3__M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP093030-CSL
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors



