

PRODUCT-DETAILS

3GKP112370-ASK

No Description Available



General Information

Product ID	3GKP112370-ASK
ABB Type Designation	M3KP 112MG 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 112MG 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI) Poland (PL)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdbeb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	4.00 kW	1454 r/min	8.70 A	0.750	88.70 %	26.30 N-m	7.50
D	T4	50 Hz	230 V	4.00 kW	1454 r/min	15.10 A	0.750	88.70 %	26.30 N-m	7.50
Y	T4	50 Hz	380 V	4.00 kW	1446 r/min	8.90 A	0.770	88.60 %	26.40 N-m	6.80
D	T4	50 Hz	220 V	4.00 kW	1446 r/min	15.40 A	0.770	88.60 %	26.40 N-m	6.80
Y	T4	50 Hz	415 V	4.00 kW	1458 r/min	8.60 A	0.730	88.90 %	26.20 N-m	7.90
Y	T4	60 Hz	460 V	4.00 kW	1760 r/min	7.60 A	0.740	89.80 %	21.70 N-m	8.80

Gas Group	IIB
Gross Weight	76 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.6 % Partial Load (75%) 89.5 % Partial Load (50%) 89.4 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.8 % Partial Load (75%) 89.7 % Partial Load (50%) 88.3 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	71 kg
Product Type	3KP3__M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP112330-ASL
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

