

PRODUCT-DETAILS

3GKP114330-CEJ

No Description Available



General Information

Product ID	3GKP114330-CEJ
ABB Type Designation	M3KP 112MC 8
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 112MC 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6206-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	T4	50 Hz	500 V	1.50 kW	709 r/min	3.30 A	0.650	79.60 %	19.90 N·m	3.60
D	T4	60 Hz	575 V	1.50 kW	862 r/min	3.00 A	0.620	83.90 %	19.90 N·m	4.00

Gas Group	IIB
Gross Weight	77 kg
IC Class	IC411

IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 79.6 % Partial Load (75%) 81.1 % Partial Load (50%) 80.8 %
IE Class Data (60 Hz)	IE Class IE2 Full Load (100%) 83.9 % Partial Load (75%) 84.4 % Partial Load (50%) 83.1 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor Product ID	3GKP114330-BEJ
Product Name	3-Phase squirrel cage motor
Product Net Weight	72 kg
Product Type	3KP0__M3JP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP114330-CEH
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	E
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



