

PRODUCT-DETAILS

3GKP131220-CDJ

No Description Available



General Information

Product ID	3GKP131220-CDJ
ABB Type Designation	M3KP 132SMB 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3KP 132SMB 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
EX-Protection	Exdbeb
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	5.50 kW	2865 r/min	5.80 A	0.860	87.00 %	18.30 N-m	6.90
D	T4	50 Hz	400 V	5.50 kW	2865 r/min	10.00 A	0.860	87.00 %	18.30 N-m	7.00
D	T4	60 Hz	460 V	5.50 kW	3485 r/min	8.60 A	0.870	86.00 %	15.01 N-m	7.90

Gas Group	IIB
Gross Weight	98 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 87.0 % Partial Load (75%) 87.6 % Partial Load (50%) 87.0 %
IE Class Data (60 Hz)	IE Class IE1 Full Load (100%) 86.0 % Partial Load (75%) 85.3 % Partial Load (50%) 82.9 %
IM Class	IMB14 IM3601
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GKP131220-BDJ
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	93 kg
Product Type	3KPO__M3JP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP131220-CDH
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



