

PRODUCT-DETAILS

3GKP161440-ASH

HIGH OUTPUT



General Information

Product ID	3GKP161440-ASH
ABB Type Designation	M3KP 160MLD 2
Catalog Description	HIGH OUTPUT

Additional Information

ABB Type Designation	M3KP 160MLD 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6309/C3
Bearing NDE	6309/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	400 V	22.00 kW	2929 r/min	39.00 A	0.900	91.20 %	71.70 N·m	7.90
D	T4	50 Hz	230 V	22.00 kW	2933 r/min	67.70 A	0.900	91.20 %	71.60 N·m	7.80
Y	T4	50 Hz	415 V	22.00 kW	2935 r/min	36.80 A	0.890	91.20 %	71.50 N·m	7.50

Gross Weight	243 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE1 Full Load (100%) 91.2 % Partial Load (75%) 91.5 % Partial Load (50%) 90.6 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	HIGH OUTPUT
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	233 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Replaced Product ID (OLD)	3GKP161440-ASG
Selling Unit of Measure	piece
Service Factor	1.00
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors



