

PRODUCT-DETAILS

3GKP258238-ADG

M3KP 250SMC 2-4



General Information

Product ID	3GKP258238-ADG
ABB Type Designation	M3KP 250SMC 2-4
Catalog Description	M3KP 250SMC 2-4

Additional Information

ABB Type Designation	M3KP 250SMC 2-4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6315M/C3
Bearing NDE	6313M/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015290
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed
YY	T4	50 Hz	400 V	70.00 kW	3000 r/min
Y	T4	50 Hz	400 V	20.00 kW	1500 r/min

Gas Group	IIB
Gross Weight	500 kg
IC Class	IC411
IM Class	IMB3 IM1001
IP Class	IP55

Insulation Class	ICLF
Invoice Description	M3KP 250SMC 2-4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Number of Poles (Low)	4
Output Power	70 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	490 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Two Speed Motor	Yes
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

