

PRODUCT-DETAILS

3GKP401530-ADG

M3KP 400LC 2



General Information

Product ID	3GKP401530-ADG
ABB Type Designation	M3KP 400LC 2
Catalog Description	M3KP 400LC 2

Additional Information

ABB Type Designation	M3KP 400LC 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6317M/C3
Bearing NDE	6317M/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394
EX-Protection	Exdbeb

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	710.00 kW	2987 r/min	679.00 A	0.890	95.00 %	2270.00 N·m	7.20
D	T4	50 Hz	400 V	710.00 kW	2987 r/min	1178.00 A	0.890	95.00 %	2270.00 N·m	7.20
D	T4	50 Hz	415 V	710.00 kW	2988 r/min	1143.00 A	0.890	95.00 %	2269.00 N·m	7.90

Gross Weight	3460 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.0 % Partial Load (75%) 94.8 % Partial Load (50%) 93.9 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 400LC 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	3420 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class	T4
Default	
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

