



PRODUCT-DETAILS

3GLP283250-BDG

M3LP 280SME 6

General Information

Product ID	3GLP283250-BDG
ABB Type Designation	M3LP 280SME 6
Catalog Description	M3LP 280SME 6

Additional Information

ABB Type Designation	M3LP 280SME 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6316/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	90.00 kW	990 r/min	93.00 A	0.860	94.10 %	868.00 N·m	7.30
D	--	50 Hz	400 V	90.00 kW	990 r/min	160.00 A	0.860	94.10 %	868.00 N·m	7.30
D	--	50 Hz	415 V	90.00 kW	991 r/min	156.00 A	0.850	94.30 %	867.00 N·m	7.90

Gross Weight	810 kg
IC Class	IC71W
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 94.1 % Partial Load (75%) 94.5 % Partial Load (50%) 94.3 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3LP 280SME 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	790 kg

Product Type	3LP2__water_cooled_motor_IE2
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Water Cooled Motors → IE2 Water Cooled Motors