



PRODUCT-DETAILS

3GLP312810-ADG

M3LP 315KHA 4

General Information

Product ID	3GLP312810-ADG
ABB Type Designation	M3LP 315KHA 4
Catalog Description	M3LP 315KHA 4

Additional Information

ABB Type Designation	M3LP 315KHA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	315.00 kW	1485 r/min	317.00 A	0.870	95.60 %	2025.00 N-m	6.20
D	--	50 Hz	400 V	315.00 kW	1485 r/min	546.00 A	0.870	95.60 %	2025.00 N-m	6.20
D	--	50 Hz	415 V	315.00 kW	1486 r/min	532.00 A	0.860	95.80 %	2025.00 N-m	6.70

Gross Weight	1510 kg
IC Class	IC71W
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.6 % Partial Load (75%) 96.0 % Partial Load (50%) 96.0 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3LP 315KHA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor

Product Net Weight	1490 kg
Product Type	3LP2__water_cooled_motor_IE2
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Water Cooled Motors → IE2 Water Cooled Motors