



PRODUCT-DETAILS

3GLP353430-BDG

Water cooled motor

General Information

Product ID	3GLP353430-BDG
ABB Type Designation	M3LP 355MLC 6
Catalog Description	Water cooled motor

Additional Information

ABB Type Designation	M3LP 355MLC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6322/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	355.00 kW	991 r/min	370.00 A	0.840	95.60 %	3420.00 N-m	6.60
D	--	50 Hz	400 V	355.00 kW	991 r/min	638.00 A	0.840	95.60 %	3420.00 N-m	6.60
D	--	50 Hz	415 V	355.00 kW	992 r/min	621.00 A	0.830	95.70 %	3417.00 N-m	7.10

Gross Weight	1780 kg
IC Class	IC71W
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.6 % Partial Load (75%) 96.0 % Partial Load (50%) 96.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	Water cooled motor
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1750 kg

Product Type	3LP2__water_cooled_motor_IE2
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Water Cooled Motors → IE2 Water Cooled Motors