



PRODUCT-DETAILS

3GLP404520-BDG

M3LP 400LB 8

General Information

Product ID	3GLP404520-BDG
ABB Type Designation	M3LP 400LB 8
Catalog Description	M3LP 400LB 8

Additional Information

ABB Type Designation	M3LP 400LB 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6324/C3
Bearing NDE	6319/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
D	--	50 Hz	400 V	450.00 kW	742 r/min	806.00 A	0.840	93.50 %	5791.00 N·m	6.50
D	--	50 Hz	415 V	450.00 kW	743 r/min	796.00 A	0.820	93.50 %	5783.00 N·m	6.90

Gross Weight	3240 kg
IC Class	IC71W
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 93.5 % Partial Load (75%) 93.8 % Partial Load (50%) 93.6 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3LP 400LB 8
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	3200 kg
Product Type	3LP2__water_cooled_motor_IE2
Quote Only	No

Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	D-End right side
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Water Cooled Motors → IE2 Water Cooled Motors