



PRODUCT-DETAILS

3GLP453530-BDG

No Description Available

General Information

Product ID	3GLP453530-BDG
ABB Type Designation	M3LP 450LC 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3LP 450LC 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6326/C3
Bearing NDE	6322/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015399
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	1050.00 kW	993 r/min	1042.00 A	0.870	96.90 %	10097.00 N·m	7.40
D	--	50 Hz	400 V	1050.00 kW	993 r/min	1797.00 A	0.870	96.90 %	10097.00 N·m	7.40
D	--	50 Hz	415 V	1050.00 kW	993 r/min	1752.00 A	0.860	96.90 %	10097.00 N·m	7.90

Gross Weight	4540 kg
IC Class	IC71W
IE Class Data (50 Hz)	IE Class NA Full Load (100%) 96.9 % Partial Load (75%) 97.2 % Partial Load (50%) 97.0 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	4500 kg
Product Type	3LP2__water_cooled_motor_IE2

Quote Only	No
Selling Unit of Measure	piece
Short Description	M3LP 450LC 6
Temperature Class Default	--
Terminator Box Location	D-End right side
Two Speed Motor	No
Type of Duty	S5
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Water Cooled Motors → IE2 Water Cooled Motors