

PRODUCT-DETAILS

3GMA071310-BSB

No Description Available



General Information

Product ID	3GMA071310-BSB
ABB Type Designation	M3MA 71MA 2
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 71MA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.37 kW	2903 r/min	0.88 A	0.740	73.90 %	1.21 N·m	9.30
D	--	50 Hz	230 V	0.37 kW	2902 r/min	1.54 A	0.740	73.90 %	1.21 N·m	9.30
Y	--	50 Hz	380 V	0.37 kW	2888 r/min	0.90 A	0.770	73.80 %	1.22 N·m	8.70
Y	--	50 Hz	415 V	0.37 kW	2912 r/min	0.87 A	0.720	73.90 %	1.21 N·m	9.70
Y	--	60 Hz	460 V	0.37 kW	3521 r/min	0.81 A	0.700	73.40 %	1.00 N·m	10.90

Gross Weight	19 kg
IC Class	IC410
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 73.8 % Partial Load (75%) 64.1 % Partial Load (50%) 57.1 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 73.4 % Partial Load (75%) 66.1 % Partial Load (50%) 56.5 %
IM Class	IMB5 IM3001
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	16 kg
Product Type	3MA3_M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors

