

PRODUCT-DETAILS

3GMA072330-BFB

No Description Available



General Information

Product ID	3GMA072330-BFB
ABB Type Designation	M3MA 71MC 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 71MC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	500 V	0.37 kW	1449 r/min	0.71 A	0.760	77.30 %	2.40 N·m	7.30
Y	--	60 Hz	575 V	0.37 kW	1756 r/min	0.80 A	0.720	78.20 %	2.00 N·m	8.50

Gross Weight	23 kg
IC Class	IC410

IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 77.3 % Partial Load (75%) 74.1 % Partial Load (50%) 69.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 78.2 % Partial Load (75%) 76.1 % Partial Load (50%) 70.6 %
IM Class	IMB5 IM3001
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	20 kg
Product Type	3MA3__M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	F

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors

