

PRODUCT-DETAILS

3GMA073310-CSB

No Description Available



General Information

Product ID	3GMA073310-CSB
ABB Type Designation	M3MA 71MA 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 71MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6204-2Z/C3
Bearing NDE	6203-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.18 kW	933 r/min	0.60 A	0.640	63.90 %	1.84 N·m	4.90
D	--	50 Hz	230 V	0.18 kW	932 r/min	1.04 A	0.640	63.90 %	1.84 N·m	4.90
Y	--	50 Hz	415 V	0.18 kW	937 r/min	0.61 A	0.610	63.90 %	1.83 N·m	5.00
Y	--	60 Hz	460 V	0.18 kW	1146 r/min	0.55 A	0.580	67.50 %	1.50 N·m	5.60

Gross Weight

18 kg

IC Class	IC410
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 63.9 % Partial Load (75%) 59.5 % Partial Load (50%) 52.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 67.5 % Partial Load (75%) 62.4 % Partial Load (50%) 55.1 %
IM Class	IMB14 IM3601
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GMA073310-BSB
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	15 kg
Product Type	3MA3_M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors



