

PRODUCT-DETAILS

3GMA093310-CSB

M3MA 90MA 6



General Information

Product ID	3GMA093310-CSB
ABB Type Designation	M3MA 90MA 6
Catalog Description	M3MA 90MA 6

Additional Information

ABB Type Designation	M3MA 90MA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015100
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	0.55 kW	963 r/min	1.37 A	0.700	77.20 %	5.40 N·m	5.40
D	--	50 Hz	230 V	0.55 kW	963 r/min	2.40 A	0.700	77.20 %	5.40 N·m	5.30
Y	--	50 Hz	380 V	0.55 kW	955 r/min	1.39 A	0.730	77.20 %	5.50 N·m	5.10
Y	--	50 Hz	415 V	0.55 kW	967 r/min	1.36 A	0.680	77.20 %	5.40 N·m	5.70
Y	--	60 Hz	460 V	0.55 kW	1168 r/min	1.23 A	0.670	81.70 %	4.50 N·m	5.90

Gross Weight	51 kg
IC Class	IC410
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 77.2 % Partial Load (75%) 74.8 % Partial Load (50%) 70.3 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 81.7 % Partial Load (75%) 79.5 % Partial Load (50%) 76.5 %
IM Class	IMB14 IM3601
IP Class	IP69
Insulation Class	ICLF
Invoice Description	M3MA 90MA 6
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GMA093310-BSB
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	48 kg
Product Type	3MA3__M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors



