

PRODUCT-DETAILS

3GMA103510-CSB

No Description Available



General Information

Product ID	3GMA103510-CSB
ABB Type Designation	M3MA 100LA 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 100LA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	1.50 kW	975 r/min	3.80 A	0.640	82.50 %	14.70 N·m	6.70
D	--	50 Hz	230 V	1.50 kW	975 r/min	6.60 A	0.640	82.50 %	14.70 N·m	6.70
Y	--	50 Hz	380 V	1.50 kW	971 r/min	3.90 A	0.670	82.50 %	14.70 N·m	6.20
Y	--	50 Hz	415 V	1.50 kW	979 r/min	3.80 A	0.620	82.50 %	14.60 N·m	7.00
Y	--	60 Hz	460 V	1.50 kW	1178 r/min	3.40 A	0.620	88.50 %	12.10 N·m	7.50

Gross Weight	63 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 82.5 % Partial Load (75%) 81.6 % Partial Load (50%) 77.7 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 88.5 % Partial Load (75%) 87.9 % Partial Load (50%) 84.6 %
IM Class	IMB14 IM3601
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GMA103510-BSB
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	58 kg
Product Type	3MA3__M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors



