

PRODUCT-DETAILS

3GMA112510-ASB

No Description Available

"No longer for sale" replaced by 3GMA112310-



General Information

Product ID	3GMA112510-ASB
ABB Type Designation	M3MA 112LA 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 112LA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2Z/C3
Bearing NDE	6205-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	4.00 kW	1452 r/min	8.30 A	0.780	88.60 %	26.30 N-m	8.00
D	--	50 Hz	230 V	4.00 kW	1452 r/min	14.40 A	0.780	88.60 %	26.30 N-m	8.00
Y	--	50 Hz	380 V	4.00 kW	1443 r/min	8.60 A	0.800	88.60 %	26.40 N-m	7.30
Y	--	50 Hz	415 V	4.00 kW	1459 r/min	8.00 A	0.780	88.60 %	26.20 N-m	8.50
Y	--	60 Hz	460 V	4.00 kW	1770 r/min	7.30 A	0.760	89.50 %	21.60 N-m	9.30

Gross Weight	66 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 88.6 % Partial Load (75%) 88.4 % Partial Load (50%) 87.1 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.5 % Partial Load (75%) 88.3 % Partial Load (50%) 86.1 %
IM Class	IMB3 IM1001
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	61 kg
Product Type	3MA3__M3MA_IE3
Quote Only	No
Replacement Product ID (NEW)	3GMA112310-ASB
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors

