

PRODUCT-DETAILS

3GMA132510-ADB

No Description Available



General Information

Product ID	3GMA132510-ADB
ABB Type Designation	M3MA 132LA 4
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 132LA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	5.50 kW	1471 r/min	7.00 A	0.720	89.60 %	35.60 N-m	10.10
D	--	50 Hz	400 V	5.50 kW	1472 r/min	12.00 A	0.720	89.60 %	35.60 N-m	10.10
D	--	50 Hz	380 V	5.50 kW	1468 r/min	12.00 A	0.760	89.60 %	35.70 N-m	9.50
D	--	50 Hz	415 V	5.50 kW	1474 r/min	12.10 A	0.690	89.60 %	35.60 N-m	10.40
D	--	60 Hz	460 V	5.50 kW	1777 r/min	10.80 A	0.700	91.70 %	29.50 N-m	11.20

Gross Weight	78 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 89.6 % Partial Load (75%) 89.2 % Partial Load (50%) 87.2 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 91.7 % Partial Load (75%) 91.2 % Partial Load (50%) 89.6 %
IM Class	IMB3 IM1001
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	73 kg
Product Type	3MA3_M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class Default	--
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors

