

PRODUCT-DETAILS

3GMA133510-CDB

No Description Available



General Information

Product ID	3GMA133510-CDB
ABB Type Designation	M3MA 132LA 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 132LA 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	690 V	3.00 kW	973 r/min	4.30 A	0.650	85.60 %	29.40 N·m	6.40
D	--	50 Hz	400 V	3.00 kW	974 r/min	7.50 A	0.650	85.60 %	29.40 N·m	6.40
D	--	50 Hz	415 V	3.00 kW	975 r/min	7.70 A	0.610	85.60 %	29.30 N·m	6.60
D	--	60 Hz	460 V	3.00 kW	1178 r/min	6.60 A	0.630	89.50 %	24.30 N·m	7.00

Gross Weight

72 kg

IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 85.6 % Partial Load (75%) 85.6 % Partial Load (50%) 83.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.5 % Partial Load (75%) 89.9 % Partial Load (50%) 87.6 %
IM Class	IMB14 IM3601
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Pre Modified Motor	3GMA133510-BDB
Product ID	
Product Name	3-Phase squirrel cage motor
Product Net Weight	67 kg
Product Type	3MA3__M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Temperature Class	--
Default	
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors



