

PRODUCT-DETAILS

3GMA133520-BSB

No Description Available



General Information

Product ID	3GMA133520-BSB
ABB Type Designation	M3MA 132LB 6
Catalog Description	No Description Available

Additional Information

ABB Type Designation	M3MA 132LB 6
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6208-2Z/C3
Bearing NDE	6208-2Z/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	--	50 Hz	400 V	4.00 kW	973 r/min	9.40 A	0.690	86.80 %	39.20 N·m	6.00
D	--	50 Hz	230 V	4.00 kW	972 r/min	16.30 A	0.690	86.80 %	39.20 N·m	6.00
Y	--	50 Hz	380 V	4.00 kW	968 r/min	9.40 A	0.730	86.80 %	39.40 N·m	5.60
Y	--	50 Hz	415 V	4.00 kW	975 r/min	9.50 A	0.660	86.80 %	39.10 N·m	6.20
Y	--	60 Hz	460 V	4.00 kW	1175 r/min	8.20 A	0.680	89.50 %	32.40 N·m	6.60

Gross Weight	79 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 86.8 % Partial Load (75%) 87.0 % Partial Load (50%) 85.8 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 89.5 % Partial Load (75%) 90.4 % Partial Load (50%) 90.1 %
IM Class	IMB5 IM3001
IP Class	IP69
Insulation Class	ICLF
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Order Multiple	1 piece
Package Level 1 Units	0 carton
Product Name	3-Phase squirrel cage motor
Product Net Weight	74 kg
Product Type	3MA3__M3MA_IE3
Quote Only	No
SCIP	e37e4277-a607-4067-93d4-6976e59c44b8 Finland (FI)
Selling Unit of Measure	piece
Stocked At (Warehouses)	Menden, Germany
Temperature Class Default	--
Terminator Box Location	N-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S

Categories

Motors and Generators → IEC Low Voltage AC Motors → Washdown Motors → IEC Food Safe Stainless Steel Motors



