

PRODUCT-DETAILS

3GQA101501-CSA

M2QA 100L2A



General Information

Product ID	3GQA101501-CSA
ABB Type Designation	M2QA100L2A
Catalog Description	M2QA 100L2A

Additional Information

ABB Type Designation	M2QA100L2A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6206-2RS/C3
Bearing NDE	6206-2RS/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor
D	--	50 Hz	220-240 V	3.00 kW	2890 r/min	6.03 A	0.880
Y	--	50 Hz	380-420 V	3.00 kW	2890 r/min	10.49 A	0.880
Y	--	60 Hz	440-480 V	3.45 kW	3470 r/min	6.12 A	0.890

Gross Volume	0.21 dm ³
Gross Weight	35 kg
IC Class	IC411
IM Class	IMB14 IM3601

IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 100L2A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Product Main Type	M2QA 100
Product Name	3 PHASE AC MOTOR
Product Net Height	270 mm
Product Net Length	380 mm
Product Net Weight	32 kg
Product Net Width	200 mm
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	65 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

