

PRODUCT-DETAILS

3GQA111301-HDA

M2QA 112M2A



General Information

Product ID	3GQA111301-HDA
ABB Type Designation	M2QA112M2A
Catalog Description	M2QA 112M2A

Additional Information

ABB Type Designation	M2QA112M2A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6207-2RS/C3
Bearing NDE	6206-2RS/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	CW Clockwise

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed
D	--	50 Hz	380-420 V	4.00 kW	2900 r/min
Y	--	50 Hz	660-690 V	4.00 kW	2900 r/min
D	--	60 Hz	440-480 V	4.60 kW	

Gross Weight	44 kg
IC Class	IC411
IM Class	IMB35 IM2001
IP Class	IP55

Insulation Class	ICLF
Invoice Description	M2QA 112M2A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Moment of Inertia	0.00671 kg/m³
Number of Poles (High)	2
Product Main Type	M2QA 112
Product Name	3 PHASE AC MOTOR
Product Net Weight	41 kg
Product Type	QA__Cast_Iron_motor
Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	67 dB(A)
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

