

PRODUCT-DETAILS

3GQA113301-BSA

M2QA 112M6A



General Information

Product ID	3GQA113301-BSA
ABB Type Designation	M2QA112M6A
Catalog Description	M2QA 112M6A

Additional Information

ABB Type Designation	M2QA112M6A
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6207-2RS/C3
Bearing NDE	6206-2RS/C3
Country of Origin	China (CN)
Customs Tariff Number	85015220
Direction of Rotation	Both sides

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency
D	--	50 Hz	220-240 V	2.20 kW	940 r/min	5.23 A	0.760	80.00 %
Y	--	50 Hz	380-420 V	2.20 kW	940 r/min	9.10 A	0.760	80.00 %
Y	--	60 Hz	440-480 V	2.53 kW	1145 r/min	5.42 A	0.770	80.00 %

Gross Weight	42 kg
IC Class	IC411
IM Class	IMB5 IM3001

IP Class	IP55
Insulation Class	ICLF
Invoice Description	M2QA 112M6A
Lubrication	For life
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	6
Product Main Type	M2QA 112
Product Name	3 PHASE AC MOTOR
Product Net Weight	39 kg
Product Type	QA__Cast_Iron_motor
Quote Only	No
Replaced Product ID (OLD)	QY113301-BSA
Selling Unit of Measure	piece
Standards	IEC 60034-1
Starting of Motor	Direct Online
Temperature Class Default	--
Terminator Box Location	D-End top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	S
WEEE Category	Product Not in WEEE Scope

Categories

Motors and Generators → IEC Low Voltage AC Motors → General Performance Motors → IE1 Standard Efficiency Cast Iron Motors

